## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:
WHAT IS CLAIMED IS:

1. (Previously Presented). A method of lowering the Young's modulus of a silicone hydrogel to between about 20 and about 180 psi or  $\tan \delta$  of a silicone hydrogel to less than about 0.1 to no more than about 0.3, measured at a frequency of 1 Hz and a temperature of 25°C, said method comprising the step of incorporating in said hydrogel, a mono-alkyl terminated polydiorganosiloxane monomer having the structure:

where b = 0 to 100;  $R_{58}$  is a monovalent group containing at least one ethylenically unsaturated moiety;  $R_{59}$  is independently a monovalent alkyl, or aryl group, which may be further substituted with alcohol, amine, ketone, carboxylic acid or ether group;  $R_{60}$  is a monovalent alkyl, or aryl group, which may be further substituted with alcohol, amine, ketone, carboxylic acid or ether groups; and  $R_{61}$  is independently alkyl or aromatic, or a monovalent siloxane chain comprising from 1 to 100 repeating Si-O units.

- 2. (original). The method of claim 1, wherein b is about 4 to about 16, R<sub>58</sub> is a monovalent group containing at least one styryl, vinyl, or methacrylate moiety, R<sub>59</sub> is methyl, R<sub>60</sub> is C<sub>3-8</sub> alkyl group, and R<sub>61</sub> is methyl.
- 3. (original). The method of claim 1, wherein b is about 8 to about 10, R<sub>58</sub> is a monovalent group containing at least one styryl, vinyl, or methacrylate moiety, 14:39 is methyl, R<sub>60</sub> is C<sub>3-8</sub> alkyl group, and R<sub>61</sub> is methyl.

4. (original). The method of claim 1, wherein b is about 4 to about 16,  $R_{58}$  is a methacrylate moiety; each  $R_{59}$  is methyl; and  $R_{60}$  is a butyl group.

+

- 5. (original). The method of claim 1, wherein b is about 8 to about 10,  $R_{58}$  is a methacrylate moiety; each  $R_{59}$  is methyl,  $R_{60}$  is a butyl group, and  $R_{61}$  is methyl.
- 6. (Previously Presented). The method of claim 1, wherein about 2 to about 70 % wt, based on total weight of reactive monomer components from which the silicone hydrogel is made, of the mono-alkyl terminated polydiorganosiloxane is incorporated in said silicone hydrogel.
- 7. (Previously Presented). The method of claim 1, wherein about 4 to about 50 % wt, based on the total weight of reactive monomer components from which the silicone hydrogel is made, of the mono-alkyl terminated polydiorganosiloxane is incorporated in said silicone hydrogel.
- 8. (Previously Presented). The method of claim 1, wherein about 8 to about 40 % wt, based on the total weight of reactive monomer components from which the silicone hyd togel is made, of the mono-alkyl terminated polydiorganosiloxane is incorporated in said silicone hydrogel.
- (original). The method of claim 1, wherein said silicone hydrogel additionally comprises a silicone-containing monomer other than that of claim 1 and having the structure:

$$R_{51} = (CH_3)_r \times (CH_2)_p - Si - (OSiR_{52}R_{53}R_{54})_q$$

wherein  $R_{51}$  is H,  $C_{1-5}$ alkyl, or an ethylenically unsaturated moiety, q is 1, 2, or 3 and for each q,  $R_{52}$ ,  $R_{53}$  and  $R_{54}$  is independently an alkyl group, an aromatic group or a monovalent

siloxane chain comprising from 1 to 100 repeating Si-O units, p is 1 to 10, r = (3-q), X is O or NR<sub>55</sub>, where R<sub>55</sub> is H or a monovalent alkyl group with 1 to 4 carbons, a is 0 or 1, and L is a divalent linking group.

- 10. (original). The method of claim 1, wherein said silicone hydrogel additionally comprises 3-methacryloxypropyltris (trimethylsiloxy) silane.
- 11. (original). The method of claim 9, wherein each of  $R_{52}$ ,  $R_{53}$ , and  $R_{54}$  is independently ethyl, methyl, benzyl or phenyl.
- 12. (Previously presented). The method of claim 1 wherein said silicone hydrogel has a Young's modulus of less than about 154 psi and a tan  $\delta$  of equal to or less than about 0.5 at a frequency of 1 Hz at 25°C.
- 13. (Previously presented). The method of claim 12, wherein the Young's modulu; is less than about 130 psi.
- 14. (Previously presented). The method of claim 12, wherein the Young's modulus is less than about 100 psi.
- 15. (Previously presented). The method of claim 12, wherein the Young's modulus is less than about 70 psi.
- 16. (Previously presented). The method of claim 12, wherein the Young's modulus is less than about 45 psi.
- 17. (Previously presented). The method of claim 12, further comprising an O<sub>2</sub> Dk greater than about 40 barrer.
- 18. (Previously Presented). The method of claim 12, 13, or 17, further comprising about 2-70 % wt, based on the total weight of reactive monomer components from which the silicone hydrogel is made, of said mono-alkyl terminated polydiorganosiloxane.

- 19. (Previously presented). The method of claim 18, wherein b = 4 to 16,  $R_{58}$  is a monovalent group containing at least one styryl, vinyl, or methacrylate moiety, each  $R_{59}$  is methyl,  $R_{60}$  is a  $C_{3.8}$  alkyl group, and  $R_{61}$  is methyl.
- 20. (Previously presented). The method of claim 18, wherein b = 8 to 10,  $R_{58}$  is a methacrylate moiety; each  $R_{59}$  is methyl;  $R_{60}$  is a butyl group, and  $R_{61}$  is methyl.
- 21. (Previously Presented). The method of claim 18, wherein the mono-alkyl term nated polydiorganosiloxane is a monomethacryloxypropyl terminated polydimethylsiloxane.
- (Canceled).
- 23. (Previously presented). The method of claim 18, having a Young's modulus of about 40-130 psi.

Claims 24-74 (Canceled).

75. (Previously Presented). A method of lowering the Young's modulus of a silicone hydrogel to between about 20 and about 180 psi and  $\tan \delta$  of a silicone hydrogel to less than about 0.1 to no more than about 0.3, measured at a frequency of 1 Hz and a temperature of 25°C, said method comprising the step of incorporating in said hydrogel, a mono-alkyl terminated polydiorganosiloxane monomer having the structure:

where b=0 to 100;  $R_{58}$  is a monovalent group containing at least one ethylenically unsaturated moiety;  $R_{59}$  is independently a monovalent alkyl, or aryl group, which may be further substituted with alcohol, amine, ketone, carboxylic acid or ether group;  $R_{60}$  is a monovalent alkyl, or aryl group, which may be further substituted with alcohol, amine, ketone, carboxylic acid or ether groups; and  $R_{61}$  is independently alkyl or aromatic, or a monovalent siloxane chain comprising from 1 to 100 repeating Si-O units.

76. (Currently Amended). The method of claim 75, wherein said silicone hydrogel additionally comprises a silicone-containing monomer other than the mono-alkyl termin ned polydiorganosiloxane monomer of claim 1 and having the structure:

$$R_{51} = (CH_3)_r \times (CH_2)_p - Si - (OSiR_{52}R_{53}R_{54})_q$$

wherein  $R_{51}$  is H,  $C_{1-5}$ alkyl, or an ethylenically unsaturated moiety, q is 1, 2, or 3 and for each q,  $R_{52}$ ,  $R_{53}$  and  $R_{54}$  is independently an alkyl group, an aromatic group or a monovalent siloxane chain comprising from 1 to 100 repeating Si-O units, p is 1 to 10, r = (3-q), X i : O or NR<sub>55</sub>, where  $R_{55}$  is H or a monovalent alkyl group with 1 to 4 carbons, a is 0 or 1, and L is a divalent linking group.

- 77. (original). The method of claim 75, wherein said silicone hydrogel additionally comprises 3-methacryloxypropyltris (trimethylsiloxy) silane.
- 78. (original). The method of claim 76, wherein each of  $R_{52}$ ,  $R_{53}$ , and  $R_{54}$  is independently ethyl, methyl, benzyl or phonyl.
- 79. (original). The method of claim 75 wherein Young's modulus is lowered to less than about 100 psi and tan  $\delta$  of equal to or less than about 0.25 at a frequency of 1 Hz at 25°C.

80. (original). The method of claim 75 wherein Young's modulus is lowered to less than about 80 psi and  $\tan \delta$  of equal to or less than about 0.25 at a frequency of 1 Hz at 25°C.